

Grotan® F 30



Schülke & Mayr

TECHNICAL LEAFLET

F30

PRESERVATIVE FOR TECHNICAL PRODUCTS

- Fungicidal effect
- Broad, balanced spectrum of effect against yeasts and moulds
- Good immediate effect
- Free from nitrate, nitrosing agents, formaldehyde/ formaldehyde donor compounds

Technical data

		CAS-Nr.
Actives	3-Iodo-2-propynylbutylcarbamate	55406-53-6
Appearance	Clear, nearly colourless – yellow liquid	
Density (20 °C)	1.140 – 1.151 g/ml	
Viscosity (DIN 53 211)	Flow time approx. 37 sec (20 °C)	
Odour	characteristic	
Refractive index (20 °C)	1.454 – 1.466	
Boiling point	approx. 230 °C	
Flashpoint (ISO 2719)	> 100 °C	

Use concentration

		Recommended dosage	
Watermiscable metalworking fluids	0.15 – 0.30 g/kg	(0.015 – 0.030 %)	The optimum use level should be evaluated by means of a repeated challenge test (e.g. BOKO-Test by S&M – Technical and Microbiological dept). Use biocides safely. Always read the label and product information before use.
Technical emulsions	0.15 – 0.30 g/kg	(0.015 – 0.030 %)	
Aqueous systems	0.15 – 0.30 g/kg	(0.015 – 0.030 %)	
System cleaners (0.015 – 0.030 % in the end dilution)	3 – 7 g/kg	(0.3 – 0.70 %)	

Instructions on application

Grotan® F 30 is suitable for the preservation of water-mixed metalworking fluids and metalworking fluid concentrates. When using in water-mixed metalworking fluids and metalworking fluid concentrates without adequate bacteriostatic effect, the use of bactericides, e.g. **Grotan® BK**, **Grotan® WS**, **Grotan® OK**, **Grotan® OX**, or **Grotan® TK 5** is recommended. **Grotan® F 30** can be used in the pH ranges 3 to 11. **Grotan® F 30** should be incorporated at temperatures lower than 40 °C in order to prevent possible losses of effect. In order to avoid microbial growth and the resultant consumption of preservative from the outset, it is advisable to add **Grotan® F 30** to the fresh mix of metalworking fluid. More can be added at weekly to fortnightly intervals, depending on the discharge of the metalworking fluid. When adding more **Grotan® F 30**, it should be added at a point with good turbulence in order to ensure good distribution in the system. Before refilling the plant, system cleaning is recommended (e.g. with **Grotanol®**).

Microbiological efficacy

The efficacy of the product has been tested against the following microorganisms according to DGHM (German Society for Hygiene and Microbiology) – MIC in % of the product.

Fungi	MIC	Yeasts	MIC
Aspergillus niger	0.0006	Candida albicans	0.0012
Rhodotorula rubra	0.0006		
Aureobasidium pullulans	0.0002		
Fusarium oxysporum	0.0006		
Geotrichum candidum	0.0006		
Penicillium expansum	0.0012		
Penicillium funiculosum	0.0006		
Sclerophoma pityophila	0.0001		
Trichophyton mentagrophytes	0.0006		
Acremonium persicinum	0.0012		
Acremonium strictum	0.0012		

Compatibility

Material compatibility	The material compatibility tests with the concentrate of Grotan® F 30 showed good compatibility with stainless steel, zinc and aluminium. Copper or copper-containing alloys may show discolouration of surfaces wetted with Grotan® F 30 concentrate. Grotan® F 30 proved to have good compatibility with plastics.
Sealants	Rubber-based sealants can cause yellow-red discolouration of Grotan® F 30 , so that preference should be given to the use of polytetrafluoroethylene seals (PTFE).

Safety & Labelling

R- and S-Phrases	R 20/22, 41, 50 S 26, 29, 37/39
Labelling	Xn (Harmful) N (Dangerous for the environment)
For further hazard instructions and safety advice please refer to the actual material safety data sheet.	

Environmental information

At a sufficient degree of dilution, all components of **Grotan® F 30** are completely biodegradable. Experience has shown that dilutions of **Grotan® F 30** do not interfere with the operation of municipal sewage treatment plants. **Grotan® F 30** contains no organic chlorine compounds. A slight effect on the AOX value in waste water may occur as a result of the iodine content in **Grotan® F 30**. The canisters and drums used by Schülke & Mayr are made of polyethylene (HDPE) and are labelled accordingly. The 1000 kg - containers are covered by a return scheme that in Europe ensures collection of the used containers free of charge and appropriate re-use. The labels are made of PE. S&M packaging materials contain no PVC and can be recycled. For further information please ask for our detailed environmental report.

Listings and approvals of active ingredients

EINECS / ELINCS (Europe)
TSCA (USA)
AICS (Australia)
ECL (Corea)
DSL (Canada)
PICCS (Philippines)
ENCS (Japan)
Fullfills the requirements of the TRGS 611 (Germany)
The active agent has been notified within the scope of the BPD

Shelf life / Transport / Storage

Shelf life	12 months
Dangerous good	UN 3082
Package sizes	10 kg, 200 kg, 1000 kg
Storage	Protect from frost, heat and direct sunlight. Store at room temperature in the original container.

Schülke & Mayr subsidiaries in:

Belgium

S.A. Schülke & Mayr Belgium N.V.
B-1830 Machelen
Telephone 02-479 73 35
Telefax 02-479 99 66

China

Schülke & Mayr GmbH
Shanghai Representative Office
Shanghai 200041
Telephone 021-62 17 29 95
Telefax 021-62 17 29 97

Italy

Schülke & Mayr Italia S.r.l.
I-20148 Milano
Telephone 02-40 21 820
Telefax 02-40 21 829

Malaysia

Schülke & Mayr Asia Sdn Bhd
46000 Petaling Jaya
Telephone 03-77 83 56 98
Telefax 03-77 84 79 31

Netherlands

Schülke & Mayr Benelux B.V.
NL-2003 LM-Haarlem
Telephone 023-535 26 34
Telefax 023-536 79 70

Singapore

Schülke & Mayr Asia Pte Ltd
Singapore 768767
Telephone 62 57 23 88
Telefax 62 57 93 88

Switzerland


Schülke & Mayr AG
CH-8001 Zürich
Telephone 01-252 98 02
Telefax 01-252 98 27

United Kingdom

Schülke & Mayr UK Ltd.
GB-Sheffield S9 1AT
Telephone 01142-54 35 00
Telefax 01142-54 35 01

Other Distributors in:

Argentina · Australia · Austria · Belarus · Benin · Brazil · Bulgaria · Canada · Croatia · Czech Republic · Denmark · Egypt · Estonia · Finland · France · Ghana · Greece · Hong Kong · Hungary · India · Indonesia · Iran · Israel · Japan · Jordan · Korea · Kuwait · Latvia · Lebanon · Lithuania · Macedonia · Malaysia · New Zealand · Nigeria · Norway · Oman · Philippines · Poland · Portugal · Russia · Saudi Arabia · Slovakia · Slovenia · South-Africa · Spain · Sweden · Syria · Taiwan · Thailand · Turkey · Ukraine · United Arab Emirates · USA · Vietnam · Yemen · Yugoslavia



Our recommendations regarding our products are based on in-depth scientific testing in our Research Department, they are given in good faith, but no liability can be derived from them. In other respects our Conditions of Sale and Supply apply.

Schülke & Mayr GmbH
D-22840 Norderstedt
Tel. +49 40 521 00-0
Fax +49 40 521 00-244
www.schuelke-mayr.com
sai@schuelke-mayr.com